

ROADS AND PAVINGS

Item	Unit	Total rate £
Excluding site overheads and profit		
ROADS - cont'd		
Macadam roadway over 1000 m²		
Excavate 350 mm for pathways or roadbed; bring to grade; lay 100 well-rolled hardcore; lay 150 mm Type 1 granular material; lay precast edgings kerbs 50 x 150 on both sides; including foundations haunched one side in 11.5 N/mm ² concrete with all necessary formwork; machine lay surface of 90 mm macadam 60 mm base course and 30 mm wearing course; all disposal off site		
1.50 m wide	m	92.00
2.00 m wide	m	97.00
3.00 m wide	m	137.00
4.00 m wide	m	167.00
5.00 m wide	m	198.00
6.00 m wide	m	229.00
7.00 m wide	m	260.00
Macadam roadway between 400 and 1000 m²		
Excavate 350 mm for pathways or roadbed; bring to grade; lay 100 well-rolled hardcore; lay 150 mm Type 1 granular material; lay precast edgings kerbs 50 x 150 on both sides; including foundations haunched one side in 11.5 N/mm ² concrete with all necessary formwork; machine lay surface of 90 mm macadam 60 mm base course and 30 mm wearing course; all disposal off site		
1.50 m wide	m	99.00
2.00 m wide	m	115.00
3.00 m wide	m	151.00
4.00 m wide	m	186.00
5.00 m wide	m	222.00
6.00 m wide	m	258.00
7.00 m wide	m	294.00
CAR PARKS		
Excavate 350 mm for pathways or roadbed to receive surface 100 mm thick priced separately; bring to grade; lay 100 well-rolled hardcore; lay 150 mm Type 1 granular material; lay kerbs BS 7263; 125 x 255 on both sides; including foundations haunched one side in 11.5 N/mm ² concrete with all necessary formwork		
Work to falls, crossfalls and cambers not exceeding 15 degrees		
1.50 m wide	m	71.00
2.00 m wide	m	80.00
3.00 m wide	m	94.00
4.00 m wide	m	110.00
5.00 m wide	m	130.00
6.00 m wide	m	140.00
7.00 m wide	m	160.00
As above but excavation 450 mm deep and base of Type 1 at 250 mm thick		
1.50 m wide	m	137.00
2.00 m wide	m	165.00
3.00 m wide	m	222.00
4.00 m wide	m	275.00
5.00 m wide	m	335.00
6.00 m wide	m	392.00
7.00 m wide	m	449.00
To excavated and prepared base above, lay roadbase of 40 size dense bitumen macadam to BS 4987 70 thick; lay wearing course of 10 size dense bitumen macadam 30 thick; mark out car parking bays 5.0 m x 2.4 m with thermoplastic road paint; surfaces all mechanically laid		
per bay 5.0 m x 2.4 m	each	231.00
gangway	m ²	16.00
As above but stainless steel road studs 100 x 100 to BS 873:pt.4; two per bay in lieu of thermoplastic paint		
per bay 5.0 m x 2.4 m	each	231.00